

AVIVA

PRODUCT GUIDE 2024



TABLE OF CONTENTS

MODEL	PAGE	MODEL	PAGE
VENTILATION		MICROWAVE	
POWER PACK	3	OVER THE RANGE	9
AVD-306PSB3 AVM-278PS2 AVM-368PS2		AOTRM243SB AOTRM303SB	
AVP34108PS2		REFRIGERATION	
AVP44108PS2 AVP222PSB		BOTTOM MOUNT	10-11
AVP283SB UNDERCABINET	4-5	ARBM115SB ARBM150SE2	
AVA-306RS2 AVA-366RS2 AVB-306RS2		ARBM177SE ARBM188SE3 ARBM188WE3	
AVB-366RS2		FRENCH DOOR	12
AVG-306CS2 AVU243RSB		ARBM184FSE2	
AVU303RSB		TOP MOUNT	13-14
AVV-309S2 AVV-369S2		ARTM116SB ARTM142SB	
SLIDE-OUT	5	ARTM180SE	
AVS243SB AVS303SB		ARTM180WE	
CHIMNEY	6-7	WINE CELLARS + BEVERAGE CENTRES	;
AVC-306CS4 AVH-308CS2 AVH-368CS2		СОМВО	15
AVH-306CS2 AVL-306CS4 AVN-308CS3		BCS42DB3 VWD42S2	
AVN-368CS3		BEVERAGE CENTRE	15
AVO-308CS3 AVO-368CS3		CBC140SS2	
AVT242CSB		WINE CELLARS	16-17
AVT302CSB AVW-308CS2 AVW-368CS2		CWC46DS2 VPC46DS3	
ISLAND	8		
AVI-366IS4 AVI-369IS3		WARRANTY	18





POWER PACK MODEL FINISH SIZE (W x D)















AVD-306PSB3

BLACK GLASS

29 ½" x 11 ½16"

- Power: 600 CFM, 5-speeds
- Lighting: 2 LED strips, 1.5W (included)
- Controls: Electronic LED controls
- Auto delay-off timer function
- Aluminum mesh filter w/peripheral plate
- Duct transition: 6" round top
- Electrical requirements 120V / 60Hz / 3.7A

AVM-278PS2 AVM-368PS2

201-GRADE SS

27 ³/₄" x 11 ³/₈" 35 ¹/₂" x 11 ³/₈"

- Power: 860 CFM, 3-speeds
- Lighting: 2 bulbs, 3W LED (included)
- Controls: Mechanical push buttons
- 2 sets of filters: Aluminum micro hole & stainless steel baffle (included)
- Duct transition: 6" and 8" round top
- Electrical requirements 120V / 60Hz / 2.7A

AVP-34108PS2 AVP-44108PS2

430-GRADE SS

34 1/8" x 18" 44" x 18"

- Power: 1000 CFM, 4-speeds
- Lighting: 2 bulbs frosted LED 3500k (included)
- Controls: Electronic push buttons with LCD display
- Auto delay-off timer function
- 2 sets of filters: Aluminum micro hole filters and stainless steel baffle filters
- Duct transition: 8" and 10" round top
- Electrical requirements 120V / 60Hz / 3A

AVP222PSB

430-GRADE SS

22" x 11 1/4"

- Power: 200 CFM, 3-speeds
- Lighting: 2 bulbs, 2W LED (included)
- Controls: Mechanical push buttons
- Single aluminum micro hole filter (included)
- Duct transition: 6" round top
- Electrical requirements 120V / 60Hz / 1.3A

AVP283SB

430-GRADE SS

27 ¾" x 11¾"

- Power: 290 CFM, 3-speeds
- Lighting: 2 bulbs, 2W LED (included)
- Controls: Mechanical push buttons
- Single aluminum mesh filter (included)
- Duct transition: 6" round top
- Electrical requirements 120V / 60Hz / 2A





UNDERCABINET MODEL FINISH SIZE (W x D)



AVA-306RS2 AVA-366RS2

201-GRADE SS

29 ½" x 19 ¾" 35 ½" x 19 ¾"

- Power: 600 CFM, 3-speeds
- Lighting: 2 bulbs, 3W LED (included)
- Controls: Soft touch with LCD display
- Auto delay-off timer function
- Clean filter reminder
- Dual motor

- 6" hood height
- 2 sets of filters: aluminum micro hole & stainless steel baffle (included)
- Duct transition: 6" round top and 3 ¼" x 10" rear and top
- Electrical requirements 120V / 60Hz / 2.7A



AVB-306RS2 AVB-366RS2

201-GRADE SS

29 ½" x 19 ¾" 36" x 19 ¾"

- Power: 600 CFM, 3-speeds
- Lighting: 2 bulbs, 3W LED (included)
- Controls: Soft touch with LCD display
- Auto delay-off timer function
- Clean filter reminder
- Dual motor

- 6" hood height
- 2 sets of filters: aluminum micro hole & stainless steel baffle (included)
- Duct transition: 6" round top and 3 ¼" x 10" rear and top
- Electrical requirements 120V / 60Hz / 2.7A



AVG-306CS2

201-GRADE SS

29 ½" x 22"

- Power: 600 CFM, 3-speeds
- Lighting: 2 bulbs, 3W LED (included)
- Controls: Soft touch with LCD display
- Auto delay-off timer function
- Clean filter reminder
- Dual motor

- 6" hood height
- 2 sets of filters: aluminum micro hole & stainless steel baffle (included)
- Duct transition: 6" round top and 3 ¼" x 10" rear and top (included)
- Electrical requirements 120V / 60Hz / 0.5A





UNDERCABINET MODEL FINISH	SIZE (W x D)
---------------------------	--------------



AVU243RSB AVU303RSB

201-GRADE SS

S 23 ³/₄" x 18 ⁷/₈" 29 ³/₄" x 18 ⁷/₈"

- Power: 280 CFM, 2-speeds
- Lighting: 2 bulbs, 3W LED (included)
- Controls: Mechanical push buttons
- 5" hood height
- Aluminum mesh filters
- Duct transition: 3 1/4" x 10" rear and top
- Electrical requirements 110V / 60Hz / 0.45A



AVV-309S2 AVV-369S2

201-GRADE SS

29 ½" x 22" 35 ½6" x 22"

- Power: 900 CFM, 4-speeds
- Lighting: 2 bulbs, 3W LED (included)
- Controls: Soft touch with LCD display
- Auto delay-off timer function
- Clean filter reminder
- Dual motor
- 9 13/16" hood height
- Stainless steel baffle filters (included)
- Duct transition: 8" round top
- Electrical requirements 120V / 60Hz / 2.7A

SLIDE-OUT

MODEL

FINISH

SIZE (W x D)



AVS243SB AVS303SB

SS FRONT TRIM

23 %" x 11" 29 ½" x 11"

- Power: 290 CFM, 3-speeds
- Lighting: 2 bulbs, 2W LED (included)
- Controls: Mechanical slider
- \bullet Depth when open: 17 $\ensuremath{^{3}\!\!/^{\!\!\!\!4}}$ "
- Overall height: 10 ¾"
- White body with stainless front trim
- · Aluminum mesh filter
- Duct transition: 6" round top
- Electrical requirements 120V / 60Hz / 2A





CHIMNEY MODEL FINISH SIZE (W x D)



AVC-306CS4

430-GRADE SS

29 ½" x 19 ½"

- Power: 600 CFM, 4-speeds
- Lighting: 2 bulbs, 2W LED (included)
- Controls: Electronic LED controls
- Auto delay-off timer function
- 3 aluminum micro hole & stainless steel baffle (included)
- Duct transition: 6" round top
- Chimney (ducted out) for ceiling heights up to 9'0"
- Electrical requirements 120V / 60Hz / 2.7A



AVH-308CS2 AVH-368CS2

201-GRADE SS

29 ½" x 19 ¾" 35 ½" x 19 ¾"

- Power: 860 CFM, 6-speeds
- Lighting: 2 bulbs, 3W LED (included)
- Controls: Soft touch with LCD display
- Auto delay-off timer function
- Clean filter reminder
- 2 sets of filters: aluminum micro hole & stainless steel baffle (included)
- Duct transition: 6" and 8" round top
- Chimney (ducted out) for ceiling heights up to 9'0"
- Optional accessory: Chimney extension AD-884S-22 (884mm high)
- Electrical requirements 120V / 60Hz / 2.7A



AVL-306CS4

430-grade SS + Blk glass front

29 ½" x 19 ¾"

- Power: 600 CFM, 4-speeds
- Lighting: 2 bulbs, 2W LED (included)
- Controls: Electronic LED controls
- Auto delay-off timer function
- 2 sets of filters: Aluminum micro hole filters and stainless steel baffle filters (included)
- Duct transition: 6" round top
- Chimney (ducted out) for ceiling heights up to 9'0"
- Electrical requirements 120V / 60Hz / 2.7A



CHIMNEY MODEL FINISH SIZE (W x D)





201-GRADE SS

29 ½" x 19 ¾" 35 ½" x 19 ¾"

- Power: 860 CFM, 6-speeds
- Lighting: 2 bulbs, 3W LED (included)
- Controls: Soft touch with LCD Display
- Auto delay-off timer function
- Clean filter reminder
- 2 stainless steel baffle filters (included)
- Duct transition: 6" & 8" round top and 3" ¼ x 10" rear and top
- Chimney (ducted out) for ceiling heights up to 9'0"
- Optional accessory: Chimney extension AD-884S-22 (884mm high)
- Electrical requirements 120V / 60Hz / 2.7A



AVO-308CS3 AVO-368CS3

201-GRADE SS

29 ½" x 19 ¾" 35 ½" x 19 ¾"

- Power: 860 CFM, 6-speeds
- Lighting: 2 bulbs, 3W LED (included)
- Controls: Soft touch with LCD display
- Auto delay-off timer function
- Clean filter reminder
- 2 stainless steel baffle filters (inlcuded)
- Duct transition: 6" & 8" round top and 3" ¼ x 10" rear and top
- Chimney (ducted out) for ceiling heights up to 9'0"
- Optional accessory: Chimney extension AD-780-SS (780mm high)
- Electrical requirements 120V / 60Hz / 2.7A



AVT242CSB AVT302CSB

430-GRADE SS

23 %" x 19 ¼" 29 ½" x 19 ¼"

- Power: 230 CFM, 3-speeds
- Lighting: 2 bulbs, 1.5W LED (included)
- Controls: Mechanical push buttons
- · Aluminum mesh filters
- Duct transition: 6" round top
- Chimney (ducted out) for ceiling heights up to 9'0"
- Electrical requirements 110V / 60Hz / 1.15A



AVW-308CS2 AVW-368CS2

201-GRADE SS

29 ½" x 19 ¾" 35 ½" x 19 ¾"

- Power: 860 CFM, 6-speeds
- Lighting: 2 bulbs, 3W LED (included)
- Controls: Soft touch with LCD display
- Auto delay-off timer function
- Clean filter reminder
- 2 sets of filters: aluminum micro hole & stainless steel baffle (inlcuded)
- Duct transition: 6" and 8" round top
- Chimney (ducted out) for ceiling heights up to 9'0"
- Optional accessory: Chimney extension AD-800S2 (800mm high)
- Electrical requirements 120V / 60Hz / 2.7A



LAND	MODEL	FINISH	SIZE (W x D)	
_	AVI-366IS4	430-grade SS + Black glass frame	35 ¼" x 23 5%"	
BOOM.	 Power: 600 CFM, Lighting: 4 square 2W (included) Control: Electroni controls display a rear of hood Auto delay-off ting 	e LED lights , stainless so Duct trans c LED 6" round t t front and ceiling heimer function ceiling heimer function stainless so Duct trans 6" round t ceiling heimer function ceiling heimer function stainless so the properties of the properties o	 3 Aluminum micro hole filters with stainless steel peripheral plate Duct transition: 6" round top Chimney (ducted out) for ceiling heights up to 9'0' Electrical requirements 120V / 60Hz / 2.7A 	
	AVI-369IS3	201-GRADE SS	35 ½" x 23 5⁄8"	
	Power: 900 CFM, Lighting: 4 bulbs, (included) Controls: Electror with LCD display Auto delay-off tin Clean filter remine Aluminum micro- (included)	2W LED 8" round t Chimney (ceiling hei- Optional a extension der (860mm h	ducted out) for ghts up to 9'0" ccessory: Chimney AD-860S2 requirements	

 $^*Both \ AVI\text{-}366IS4 \ and \ AVI\text{-}369IS3 \ Island \ Hoods \ can be operated from the front and back side of the hood.$

VENTILATION - MODEL NUMBER NOMENCLATURE

	AVIVA
V	Ventilation
LETTER	Model name
##	Size
#	CFM (1st digit)
C/I/P	Type of Hood: Chimney, Island, Power Pack
B/S	Color: Black / Stainless Steel
#	Generation

VENTILATION WARRANTY: 1-year parts and labor





OVER THE RANGE MICROWAVE

OTR MODEL FINISH SIZE (W x D)



AOTRM243SB

Black glass + SS trims

23 1/8" x 16 3/4"

- · Capacity: 1.4 cu. ft.
- Power: 1000 Watts. 10 levels.
- Ventilation: 300 CFM, 2-speed
 Recessed handle, left-swing
- Duct transition: 3" 1/4 x 10" top and rear
- 2 aluminum mesh filters (included)
- Convertible to ductless venting Electrical requirements: with charcoal filters (included)
- Controls: Soft touch electronic with LED display
- Multiple cooking modes, including Sensor Cooking
- Overall Height: 17" 1/2
- Lighting: 2 interior lights
 - 120V / 20A / 60Hz-2450Mhz



AOTRM303SB

Black glass + SS front

29 %" x 17 %"

- Capacity: 1.7 cu. ft.
- Power: 1000 Watts, 10 levels.
- Duct transition: 3" 1/4 x 10" top and rear
- 2 aluminum mesh filters (included)
- Convertible to ductless venting Lighting: 2 interior lights with charcoal filters (included) • Electrical requirements:
- Controls: Soft touch electronic with LED display
- Ventilation: 300 CFM, 2-speed Heavy duty aluminum handle, left-swing
 - Multiple cooking modes, including Sensor Cooking
 - Overall Height: 16" 1/8

 - 120V / 20A / 60Hz-2450Mhz

23 ½" x 27" x 68"



REFRIGERATION

BOTTOM MOUNT MODEL **FINISH** SIZE (W x D x H)

ARBM115SB









- Freestanding, bottom-mount refrigerator-freezer
- Capacity: 11.5 cu.ft. (Fridge 8.3 + Freezer 3.2)
- Flat door design
- Counter-depth
- Recessed, pocket door handle
- Reversible doors
- Internal electronic soft touch controls
- Interior LED lighting
- Frost-free, multi-airflow cooling system
- 3 glass shelves
- 1 large + 2 small door bins
- Large capacity crisper and 1 deli tray
- Freezer includes 2 glass shelves and 1 drawer
- Energy Star® rated
- R600A Refrigerant gas
- Electrical requirements 120V / 60Hz / 15A



ARBM150SE2

STAINLESS STEEL

STAINLESS STEEL

27 5/8" x 26 1/2" x 67 3/4"

- Freestanding, bottom-mount refrigerator-freezer
- · Capacity: 14.8 cu.ft. (Fridge 10.6 + Freezer 4.2)
- · Slightly curved door design
- · Counter-depth
- Recessed door handles
- Reversible doors
- Door open alarm
- Internal electronic soft touch controls
- Soft interior LED Lighting
- Multi airflow, ambient cooling system
- Precise temperature control
- Super Cool and Super freeze function
- 3 adjustable glass shelves
- 3 large + 2 adjustable door bins
- · Large capacity crisper
- Freezer includes manual ice-maker with ice bin, 2 large drawers + 1 small tray
- Energy Star* rated
- R600A Refrigerant gas
- Electrical requirements 120V / 60Hz / 15A







BOTTOM MOUNT MODEL **FINISH** SIZE (W x D x H)











- Freestanding, bottom-mount refrigerator-freezer
- Capacity: 17.7 cu. ft. (Fridge 12.7 + Freezer 5)
- Flat-door design
- Metallic liner & backsplash
- Recessed door handles
- Reversible doors
- Door open alarm
- Internal electronic soft touch controls
- · Soft interior LED lighting
- Multi airflow, ambient cooling system
- Precise temperature control
- Super Cool and Super freeze function
- 3 adjustable glass shelves
- 1 large + 4 small height-adjustable door bins
- 2 large capacity crispers
- Freezer includes 2 large drawers + 2 small trays
- Energy Star® rated
- R600A Refrigerant gas
- Electrical requirements 120V / 60Hz / 15A



ARBM188SE3 ARBM188WE3 STAINLESS STEEL WHITE

29 ½" x 31" x 66 ¾"

- Freestanding, bottom-mount, single-door slide-out drawer freezer
- Capacity: 18.7 cu. ft. (Fridge 13.1 + Freezer 5.6)
- Flat-door design
- Recessed door handles
- Reversible fridge door
- Door open alarm
- Internal electronic touch controls
- Interior Lighting LED lights
- Dual temperature control system
- 2 height-adjustable glass shelves
- 1 large + 3 small height-adjustable door bins
- 2 crispers with humidity control
- Freezer includes 2 large slide-out bins (1 white + 1 clear)
- Energy Star* rated
- R600A Refrigerant gas
- Electrical requirements 120V / 60Hz / 15A



ARBM188WE3






SIZE (W x D x H) **FRENCH DOOR** MODEL **FINISH**

ARMB184FSE2







STAINLESS STEEL

29 ½" x 31" x 66 ¾"

- Freestanding, bottom-mount, French-door, slide-out drawer freezer
- Capacity: 18.4 cu. ft. (Fridge 12.8 + Freezer 5.6)
- Flat-door design
- Recessed door handles
- Internal electronic touch controls
- Door open alarm
- Interior Lighting LED lights
- Precise temperature control
- 2 height-adjustable glass shelves
- 6 large door bins (3 on each side)
- 2 crispers with humidity control • Freezer includes 2 large storage bin
- (1 white + 1 clear) • Energy Star* rated
- R600 Refrigerant gas
- Electrical requirements 120V / 60Hz / 15A







TOP MOUNT MODEL FINISH SIZE (W x D x H)



ARTM116SB STAINLESS STEEL

INLESS STEEL 23 ½" x 29" x 59 ½"

- Freestanding, top mount refrigeratorfreezer
- Capacity: 11.6 cu. ft. (Fridge 8.4 + Freezer 3.2)
- Flat door design
- Recessed door handles
- Reversible doors
- · Internal mechanical control
- Interior LED lighting
- Frost-free, multi-airflow cooling system
- 3 glass shelves
- 2 large + 4 small door bins
- + bottle/pop can holder bins
- 2 crispers
- Freezer includes 1 wire shelf and 2 large door bins
- R600A Refrigerant gas
- Electrical requirements 120V / 60Hz / 15A







ARTM142SB

STAINLESS STEEL

27-1/2" x 29-1/8" x 60"

- Freestanding, top mount refrigerator-freezer
- Capacity: 14.2 cu. ft. (Fridge 10.6 + Freezer 3.6)
- Flat door design
- Recessed door handles
- Reversible doors
- Internal electronic soft touch controls
- Interior LED lighting
- Frost-free, multi-airflow cooling system
- 3 glass shelves
- 2 large door bins
- 1 crispers
- Freezer includes 1 glass shelf and 2 large door bins
- Energy Star® rated
- R600A Refrigerant gas
- Electrical requirements 120V / 60Hz / 15A







TOP MOUNT MODEL FINISH SIZE (W x D x H)





• Electrical requirements 120V / 60Hz / 15A

REFRIGERATION - MODEL NUMBER NOMENCLATURE

Α	AVIVA
R	Refrigerator
BM/TM	Bottom-mount / Top-mount
##	Capacity
F	French Door
S/W	Stainless Steel / White
E	Energy Star
#	Generation

WARRANTY: 2-years labor and replacement parts. Additional 3-year warranty, for a total of 5 years on the sealed system (components only).





WINE CELLARS & BEVERAGE CENTRES

COMBO MODEL FINISH SIZE (W x D* x H)



BSC42DB3

BLACK + GLASS

23 ¾" x 23 ¼" x 34 ½"

- Dual-zone, temperature range per zone: 39°- 64°F / 4-18°C
- Side by side configuration
- Built in or freestanding
- Flush fit installation
- Capacity: 21 bottles + 64 cans
- Door open alarm
- High-temperature alarm
- Soft-touch electronic controls
- Made of vitrified black glass
 tinted and UV treated glass
 with Low-E argon gas
- SS Tubular Pro handle
- Interior lighting White LED
- · Stainless steel kick plate
- 6 full-extension, ball-bearing metal racks with black wooden frontage
- + 3 glass shelves • R600a Refrigerant gas



VWD42S2

SS + GLASS

23 1/8" x 23 3/4" x 34 1/2"

- Dual-zone temp. range per zone: 39° - 64°F / 4 - 18°C
- Side by side configurationEach side convertible to wine
- Each side convertible to wine or beverage cooler
- Built in or freestanding
- Flush fit installation
- Total Capacity: 42 bottles or 21 bottles + 64 cans
- Door open alarm
- High-temperature alarm
- Soft-touch electronic controls

- Seamless, stainless steel doors
- Tinted glass with Low-E: Argon gas
- SS tubular pro handle
- LED lighting color options: White, Blue, Yellow
- Stainless steel kick plate
- 12 wooden shelves with stainless steel front trim
- Includes 3 glass shelves for beverage configuration
- Sabbath mode
- R600a Refrigerant gas

^{*}Depth does not include handle.





WINE CELLARS & BEVERAGE CENTRES

WINE CELLAR

MODEL

FINISH

SIZE (W \times D* \times H)



CWC46DS2

SS + GLASS

23 ½" x 21 ½6" x 34"

- Dual-zone, temperature range per zone: 41° - 64°F / 5 - 18° C
- Built in or freestanding
- Flush fit installation
- Capacity: 46 bottles
- Seamless, stainless steel door
- Door open alarm
- High-temperature alarm
- Electronic touch controls
- UV tinted glass with Low-E Argon gas
- Brushed SS tubular curved handle
- Interior lighting White LED
- Black kick plate
- 5 soft-closing, full-extension, ball-bearing metal racks with wood front trim
- R600a Refrigerant gas



VPC46DS3

SS + GLASS

23 ¾" x 23 ½" x 34 ½"

- Dual-zone temperature range per zone: 39° - 64°F / 4 - 18°C
- Built in or freestanding
- Flush fit installation
- Capacity: 46 bottles
- Seamless, stainless steel door
- Door open alarm
- High-temperature alarm
- Soft-touch electronic controls
- Tinted glass with Low-E Argon gas
- SS Tubular Pro handle
- Interior lighting White LED
- Stainless steel kick plate
- 5 full-extension, ball-bearing wooden shelves with stainless steel front trim
- R600a Refrigerant gas

^{*}Depth does not include handle.





WINE CELLARS & BEVERAGE CENTRES

BEVERAGE CENTER MODEL FINISH SIZE (W x D* x H)



CBC140SS2 SS + GLASS 23 ½" x 21 ½" x 34"

- Single-zone, temperature range: 34° 50°F / 1 10°C
- Built in or freestanding
- Flush fit installation
- Capacity: 140 cans
- Seamless, stainless steel door
 field reversible
- Door open alarm
- High-temperature alarm

- Electronic touch controls
- UV tinted glass with Low-E Argon gas
- Brushed SS arched handle
- Interior lighting White LED
- · Black kick plate
- 3 height-adjustable glass shelves
- R600a Refrigerant gas

WINE CELLARS & BEVERAGE CENTRES - MODEL NUMBER NOMENCLATURE

VP/BS/C	(Series) Vinopazzo / Black (Noire) / C Series
C/B/WC	Cellar / Beverage / Wine Cellar
NUMBER	Capacity
S/D	Single or Dual Zone
S/B	Stainless Steel or Black
#	Generation

WARRANTY: 2-year parts and labor, 5 years on sealed system (parts only).

*Depth does not include handle.



WARRANTY

VENTILATION

We warrant our hood against defects in materials and workmanship under ordinary residential use for one (1) full year from the date of original retail purchase. This limited warranty applies to any repair and /or replacement parts. This limited warranty is not subject to improper installation, accident, misuse, neglect, fire or other external causes, alterations, repair or commercial use.

REFRIGERATION and WINE & BEVERAGE CENTRES

Aviva refrigerators, wine cellars and beverage centres carry a two (2) year limited warranty on both parts and labor. Aviva warrants for two (2) years, to the purchaser of every new unit, the cabinet and all parts thereof, to be free from defects in material or workmanship, under normal and proper use and maintenance service as specified by Aviva and upon proper installation and start-up in accordance with the instruction manual supplied with the Aviva unit. Any parts covered under this warranty that are determined by Aviva to have been defective, within the above said period, are limited to the repair or replacement, including labor charges, of defective parts or assemblies.

In addition to the 2 year warranty period stated above, Aviva warrants its hermetically sealed compressor to be free from defects in both material and workmanship, under normal and proper use and maintenance, for a period of an additional 36 months (a total of 5 years on hermetically sealed compressor). The above said extended compressor warranty applies only to hermetically sealed parts of the compressor and DOES NOT apply to any other parts or components, including, but not limited to, cabinet, paint finish, temperature control, refrigerant, metering device, motor starting equipment, fan assembly, or any other electrical component, etc.





NOTES



PRODUCT GUIDE 2024 AVIVA

T 800 361 0799 F 450 682 7943

www.distinctive-online.com info@distinctive-online.com

HEAD OFFICE & WAREHOUSE

2025 Cunard Street Laval QC H7S 2N1

WESTERN CANADA WAREHOUSE

NFI 1020 Derwent Way Delta, BC V3M 5R1

PARTS & SERVICE

service@distinctive-online.com 800 561 7265

ORDER DESK

orderdesk@distinctive-online.com